




Material Safety Data Sheet

NFPA	PPE	Transport Symbol
		

Issuing Date 04-Jun-2009

Revision Date

Revision Number 0

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Petroleum Asphalt MC Cutback
UN-No NA1999
Synonyms MC-30, MC-70, MC-250, MC-800, MC-3000

Supplier Address

Mohawk Asphalt Emulsions
6 Freemans Bridge Road
Scotia, NY 12302
TEL: 518-372-7788

Company Emergency Phone Number 1-800-328-2482

2. HAZARDS IDENTIFICATION

WARNING!

Emergency Overview

Hot liquid can cause severe burns
Vapors may be irritating to eyes, nose, throat, and lungs
May cause central nervous system depression
Combustible material
Flammable vapors can accumulate during long term heated storage of this material
May contain and release hydrogen sulfide which is a highly toxic and flammable gas
Hydrogen Sulfide (H₂S) has a rotten egg "sulfurous" odor. This odor should not be used as a warning property of toxic levels because H₂S can overwhelm and deaden the sense of smell. H₂S meter or colorimetric indicating tubes are typically used to determine the concentration of H₂S

Appearance Dark brown, Black

Physical State Semi-Solid, Liquid.

Odor Fuel oil

OSHA Regulatory Status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Potential Health Effects

Principle Routes of Exposure

Inhalation, Skin contact, Eye contact.

Acute Toxicity

Eyes
Skin

May cause irritation. Causes thermal burns.
Irritating to skin. Repeated exposure may cause skin dryness or cracking. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Hot liquid can cause severe burns.

Inhalation	May be harmful if inhaled. May cause central nervous system effects such as headache, dizziness, loss of balance and coordination, unconsciousness, coma, respiratory failure and death. Hydrogen Sulfide gas between 15 and 500 ppm can cause headache, nausea and dizziness. Continued exposure at these levels can lead to loss of reasoning and balance, difficulty in breathing, fluid in the lungs, and possible loss of consciousness. Greater than 500 ppm can cause rapid unconsciousness due to respiratory paralysis and death by suffocation. Greater than 1000 ppm can cause immediate unconsciousness and death if not promptly revived. Contains low levels of Hydrogen sulfide which may be released and can be fatal if inhaled at certain concentrations.
Ingestion	May be harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause additional effects as listed under "Inhalation".
Chronic Effects	<p>Prolonged exposure may cause chronic effects. Prolonged or repeated contact may dry skin and cause irritation. Repeated contact may cause allergic reactions in very susceptible persons. The International Agency for Research on Cancer (IARC) has determined that there is inadequate evidence that undiluted, air-refined asphalt is carcinogenic to experimental animals. Limited evidence exists that undiluted steam-refined and cracking residue asphalts is carcinogenic to animals. Additionally, IARC has concluded that there is inadequate evidence that asphalts alone are carcinogenic to humans. Repeated long term skin application of similar petroleum crudes have been shown to cause skin cancer in laboratory animals. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.</p> <p>Hydrogen sulfide (H₂S), a colorless, rotten-egg smelling, minor component of this product, can affect the body if it is inhaled or if it comes in contact with the eyes, skin, nose or throat. Odor cannot be used as an indication of its presence since exposure to H₂S causes loss of the sense of smell. Inhalation of high concentrations of hydrogen sulfide (>1000 ppm) may cause coma, convulsions, and death after a single overexposure due to its ability to be a rapidly acting systemic poison that causes respiratory paralysis. Lower and prolonged doses can cause severe respiratory tract irritation and inflammation including eye irritation and damage and central nervous system effects such as headache, fatigue, irritability, insomnia, and stomach upset. Pneumonitis (chemically induced pneumonia) can also occur.</p>
Aggravated Medical Conditions	Respiratory disorders, Skin disorders.
Environmental Hazard	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. See Section 12 for additional Ecological Information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Asphalt	8052-42-4	50-85
Kerosene	8008-20-6	15-50

Asphalt can contain hydrogen sulfide (CAS # 7783-06-4), a naturally occurring substance found in crude oil, a material from which asphalt is derived. Amounts contained in this product are considered residual, but can be released upon heating. contain traces of nickel, iron or vanadium.

4. FIRST AID MEASURES

General Advice	Show this safety data sheet to the doctor in attendance.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
Skin Contact	In case of burns, immediately cool affected skin for as long as possible with cold water. Immediate medical attention is required. If skin has bonded to clothing or other skin NEVER pull the area apart. Do not try to removed solidified material from the skin. Do not use solvents or thinners to dissolve the material. The use of vegetable oil or mineral oil is recommended for removal of this material from the skin. .
Inhalation	Move victim to fresh air. Administer oxygen if breathing is difficult and you are trained. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Rinse mouth. Drink plenty of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Consult a physician.
Notes to Physician	Keep victim warm and quiet.
Protection of First-aiders	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. FIRE-FIGHTING MEASURES

Flammable Properties	Flammable; may be ignited by heat, sparks or flames. Vapors may cause flash fire or explosion. Containers may explode when heated.
Flash Point	>103°F / 39°C
Suitable Extinguishing Media	Dry chemical, CO ₂ , water spray or regular foam. Use water spray or fog; do not use straight streams. Move containers from fire area if you can do it without risk.
Unsuitable Extinguishing Media	CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient. Do not use a solid water stream as it may scatter and spread fire.
Hazardous Combustion Products	Hydrogen sulfide , Oxides of sulfur, Nitrogen oxides (NOx), Carbon oxides.
Explosion Data	
Sensitivity to Mechanical Impact	None
Sensitivity to Static Discharge	Yes.
Specific Hazards Arising from the Chemical	Flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Those substances designated with a "P" may polymerize explosively when heated or involved in a fire. Runoff to sewer may create fire or explosion hazard. Substance may be transported hot.
Protective Equipment and Precautions for Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

<u>NFPA</u>	Health Hazard 2	Flammability 2	Stability 0	Physical and Chemical Hazards -
<u>HMIS</u>	Health Hazard 2*	Flammability 2	Physical Hazard 0	Personal Protection -

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Stop leak if you can do it without risk.
Environmental Precautions	Prevent entry into waterways, sewers, basements or confined areas.
Methods for Containment	A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Dike far ahead of liquid spill for later disposal.
Methods for Cleaning Up	Use clean non-sparking tools to collect absorbed material.
Other Information	Water spray may reduce vapor; but may not prevent ignition in closed spaces.

7. HANDLING AND STORAGE

Handling	Ensure adequate ventilation. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from heat, sparks and open flame. No smoking.
Storage	Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat and sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Asphalt 8052-42-4	TWA: 0.5 mg/m ³		Ceiling: 5 mg/m ³ Ceiling: 0.05 mg/m ³ TWA: 0.015 mg/m ³
Kerosene 8008-20-6	TWA: 200 mg/m ³ S*		TWA: 100 mg/m ³
Hydrogen sulfide 7783-06-4	STEL = 15 ppm TWA: 10 ppm	(vacated) TWA: 10 ppm (vacated) TWA: 14 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 21 mg/m ³ Ceiling: 20 ppm	IDLH: 100 ppm Ceiling: 10 ppm Ceiling: 15 mg/m ³

NIOSH IDLH: Immediately Dangerous to Life or Health

Engineering Measures	Showers Eyewash stations Ventilation systems
Personal Protective Equipment	
Eye/Face Protection	Tightly fitting safety goggles.
Skin and Body Protection	Wear protective gloves/clothing.
Respiratory Protection	None required under normal usage. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.
Hygiene Measures	When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Dark brown, Black.	Odor	Fuel oil.
Odor Threshold	No information available	Physical State	Semi-Solid, Liquid
pH	No information available		
Flash Point	>103°F / 39°C	Autoignition Temperature	242°C / 468°F
Decomposition Temperature	No information available	Boiling Point/Range	160°C / 320°F
Melting Point/Range	37.8-57.2°C / 100-135°F		
Flammability Limits in Air		Explosion Limits	No information available
Upper	6%		
Lower	0.8%		
Water Solubility	Insoluble in water	Solubility	No information available
Evaporation Rate	No information available	Vapor Pressure	12 mmHg @ 68 °F
Vapor Density	No data available	VOC Content	Not applicable

10. STABILITY AND REACTIVITY

Stability	Stable under recommended storage conditions.
Incompatible Products	Strong oxidizing agents.
Conditions to Avoid	Heat, flames and sparks. Heating can release hazardous gases.
Hazardous Decomposition Products	Hydrogen sulfide.
Hazardous Polymerization	Hazardous polymerization does not occur.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information	No acute toxicity information is available for this product.
Inhalation	There is no data available for this product. Avoid breathing vapors or mists. May cause central nervous system depression.
Eye Contact	There is no data available for this product. May cause irritation. Causes thermal burns.
Skin Contact	There is no data available for this product. May cause skin irritation and/or dermatitis. May cause sensitization of susceptible persons. Repeated exposure may cause skin dryness or cracking.
Ingestion	Low order of toxicity based on components. May be harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Asphalt	5000 mg/kg (Rat)	2000 mg/kg (Rabbit)	

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Kerosene	5000 mg/kg (Rat)	2000 mg/kg (Rabbit)	5.28 mg/L (Rat) 4 h
Hydrogen sulfide			0.701 mg/L (Rat) 4 h 0.99 mg/L (Rat) 1 h

Chronic Toxicity

Chronic Toxicity

Prolonged exposure may cause chronic effects. Prolonged or repeated contact may dry skin and cause irritation. Repeated contact may cause allergic reactions in very susceptible persons. The International Agency for Research on Cancer (IARC) has determined that there is inadequate evidence that undiluted, air-refined asphalt is carcinogenic to experimental animals. Limited evidence exists that undiluted steam-refined and cracking residue asphalts is carcinogenic to animals. Additionally, IARC has concluded that there is inadequate evidence that asphalts alone are carcinogenic to humans. Repeated long term skin application of similar petroleum crudes have been shown to cause skin cancer in laboratory animals. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.

Hydrogen sulfide (H₂S), a colorless, rotten-egg smelling, minor component of this product, can affect the body if it is inhaled or if it comes in contact with the eyes, skin, nose or throat. Odor cannot be used as an indication of its presence since exposure to H₂S causes loss of the sense of smell. Inhalation of high concentrations of hydrogen sulfide (>1000 ppm) may cause coma, convulsions, and death after a single overexposure due to its ability to be a rapidly acting systemic poison that causes respiratory paralysis. Lower and prolonged doses can cause severe respiratory tract irritation and inflammation including eye irritation and damage and central nervous system effects such as headache, fatigue, irritability, insomnia, and stomach upset. Pneumonitis (chemically induced pneumonia) can also occur.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Asphalt			Known	
Kerosene	A3			

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

NTP: (National Toxicity Program)

Known - Known Carcinogen

Target Organ Effects

Respiratory system, Skin, Central nervous system (CNS).

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Hydrogen sulfide		LC50= 0.016 mg/L Pimephales promelas 96 h LC50= 0.0448 mg/L Lepomis macrochirus 96 h		EC50 = 0.022 mg/L 96 h

Chemical Name	Log Pow
Asphalt	6
Hydrogen sulfide	25

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Should not be released into the environment. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of in accordance with local regulations.

US EPA Waste Number D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Asphalt - 8052-42-4	(hazardous constituent - no waste number)			

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name Asphalt
Hazard Class Combustible liquid
UN-No NA1999
Packing Group III
Description NA1999,Asphalt,Combustible liquid,,PG III
Emergency Response Guide Number 130

TDG

Proper Shipping Name Tars, liquid
Hazard Class 3
UN-No UN1999
Packing Group III
Description TARS, LIQUID,3,UN1999,PG III

MEX

Proper Shipping Name Tars, liquid
Hazard Class 3
UN-No UN1999
Packing Group III
Description UN1999 Tars, liquid,3,III

ICAO

UN-No UN1999
Proper Shipping Name Tars, liquid
Hazard Class 3
Packing Group III
Description Tars, liquid,3,UN1999,PG III

IATA

UN-No UN1999
Proper Shipping Name Tars, liquid
Hazard Class 3
Packing Group III
ERG Code 3L
Description UN1999,Tars, liquid,3,PG III

IMDG/IMO

Proper Shipping Name Tars, liquid

14. TRANSPORT INFORMATION

Hazard Class 3
Subsidiary Class +
UN-No UN1999
Packing Group III
EmS No. F-E, S-E
Description UN1999, Tars, liquid,3(+),PG III

RID

Proper Shipping Name Tars, liquid
Hazard Class 3
UN-No UN1999
Packing Group III
Classification Code F1
Description UN1999 Tars, liquid,3,III,RID
ADR/RID-Labels 3

ADR

Proper Shipping Name Tars, liquid
Hazard Class 3
UN-No UN1999
Packing Group III
Classification Code F1
Description UN1999 Tars, liquid,3,III

ADN

Proper Shipping Name Tars, liquid
Hazard Class 3
Packing Group III
Classification Code F1
Special Provisions 640E
Description UN1999 Tars, liquid,3,III
Hazard Labels 3
Limited Quantity LQ7
Ventilation VE01

15. REGULATORY INFORMATION**TSCA - United States Toxic Substances Control Act Section 8(b) Inventory**

Chemical Name	TSCA
Asphalt	X
Kerosene	X

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Asphalt	8052-42-4	50-85	0.1 1.0

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes

Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):.

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Asphalt		X		
Nickel oxide		X		
Hydrogen sulfide	100 lb			X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):.

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs
Hydrogen sulfide	100 lb	100 lb

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Nickel oxide	1313-99-1	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Asphalt	X	X	X	X	X
Kerosene	X	X	X		X

16. OTHER INFORMATION

Issuing Date	04-Jun-2009
Revision Date	
Revision Note	No information available

Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet